



## Automotive Aftermarket Division

### 3M 401Q Wetordry™ Paper

---

#### 1) Part Numbers

09546 - P2000

09545 - P1500

#### 2) Description and end uses

A premium wet sanding product producing a consistent fine finish.

#### 3) Physical Properties

230 mm x 138 mm sheets

Grit range : P1500-P2000

Backing : 115 gsm latex impregnated waterproof paper

Mineral : Silicon Carbide

Coating : Closed Coat

Bonding : Resinbond

Features	Advantages	Benefits
High quality backing	Flexible and conformable	Good handling with max performance
Silicon Carbide mineral	Fast initial cut	Defect removed and finish achieved quickly
P-graded	Uniform finish	Consistent high quality finish

#### 4) Directions for Use

Nib and defect removal on painted panels and other synthetic materials where a fine consistent finish is required.



# Technical Data Sheet

Effective: 04/05/2017

Supersedes: 15/06/2006

## 5) Storage

It is recommended that all Coated Abrasive products should be stored at constant levels of temperature and humidity within the ranges of 18-22°C, 50-65% RH. They should be kept away from damp (or cold) walls, windows or floors to avoid possible absorption. Equally storage adjacent to heat sources, eg steam pipes, radiators, hot air ducts, ovens, etc, should be avoided.

Product is best stored in original packaging until ready for use. Shelf life indefinite under these conditions.

## 6) Safety

Use product in accordance with normal wet sanding.

Whenever possible, sanding should be carried out in a well-ventilated area and it is strongly recommended that suitable goggles, dust mask and gloves are worn.

**3M 401Q Wetordry™ Paper is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.**

## 7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

For Additional Health and Safety Information

### Denmark

3M a/s  
Automotive Aftermarket  
Hannemanns Allé 53  
2300 København S  
Tel: 43 48 01 00  
[3mkundeservicedk@mmm.com](mailto:3mkundeservicedk@mmm.com)  
[www.3MAuto.dk](http://www.3MAuto.dk)

### Finland

Suomen 3M Oy  
Automotive Aftermarket  
Keilaranta 6  
02150 Espoo  
Tel: 09 5252 1  
[tilaukset@mmm.com](mailto:tilaukset@mmm.com)  
[www.3M.fi/autotuotteet](http://www.3M.fi/autotuotteet)



# Technical Data Sheet

Effective: 04/05/2017

Supersedes: 15/06/2006

## **Norway**

3M Norge AS  
Automotive Aftermarket  
Kanalveien 2  
2004 Lillestrøm  
Telefon: 06384  
[www.3m.no/auto](http://www.3m.no/auto)  
[kundeservice@mmm.com](mailto:kundeservice@mmm.com)

## **Sweden**

3M Svenska AB  
Automotive Aftermarket  
Bileftermarknad  
19189 Sollentuna  
Tel. 08-922100  
[kundservice@mmm.com](mailto:kundservice@mmm.com)  
[3M.se/bileftermarknad](http://3M.se/bileftermarknad)