

Technical Data Sheet

Effective: 25/3/16 Supersedes: 6/2/13

Automotive Aftermarket Division

3M Flexible Abrasive Hookit™ Sheets

1) Part Numbers

34337 : P400 34339 : P600 34340 : P800 34341 : P1000 34342 : P1200 34343 : P1500

34352 : Flexible abrasive foam pad

2) Description and end uses

Flexible coated abrasive sheet for abrasion of Lacquers, paints, plastics and polyester fillers/primers.

3) Physical Properties

Mineral : Aluminium Oxide Coating : Closed Coat Bonding : Resin Bond

Colour : Green (P400 – P600) Brown (P800 – P1000) Purple (1200 – P1500)

Grades : P400 – P1500 (FEPA)

4) Directions for Use

Flexible, conformable abrasive sheet for improved access to awkward areas. Ideal for shaping and feather edging. Ideal for hand sanding applications for critical or awkward areas such as headlight openings, around door handles, door jambs, etc. Helps to eliminate finger marks and can be used wet or dry.



Technical Data Sheet

Effective: 25/3/16 Supersedes: 6/2/13

5) Storage

It is recommended that all Coated Abrasive Products should be stored at constant levels of temperature and humidity within the ranges of 18-22°C, 50-65% RH. They should be kept away from damp (or cold) walls, windows or floors to avoid possible moisture absorption. Equally storage adjacent to heat sources e.g. steam pipes, radiators, hot air ducts, ovens, etc. should be avoided.

Product is best stored in original packaging until ready for use. Shelf Life indefinite under these conditions.

6) Safety

Whenever possible, sanding should be carried out in a well ventilated area and it is strongly recommended that suitable goggles, dust mask and gloves are worn.

Pads should not be modified in any way. They should be used only in their original size and shape, as supplied.

3M Flexible Abrasive Hookit™ Sheets are designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.



Technical Data Sheet

Effective: 25/3/16 Supersedes: 6/2/13

For Additional Health and Safety Information

Denmark

3M a/s Automotive Aftermarket Hannemanns Allé 53 2300 København S Tel: 43 48 01 00

3mkundeservicedk@mmm.com www.3MAuto.dk

Norway

3M Norge AS
Automotive Aftermarket
Kanalveien 2
2004 Lillestrøm
Telefon: 06384
www.3m.no/auto
kundeservice@mmm.com

Finland

Suomen 3M Oy
Automotive Aftermarket
Keilaranta 6
02150 Espoo
Tel: 09 5252 1
tilaukset@mmm.com
www.3M.fi/autotuotteet

Sweden

3M Svenska AB
Automotive Aftermarket
Bileftermarknad
19189 Sollentuna
Tel. 08-922100
kundservice@mmm.com
3M.se/bileftermarknad