

# CS Foam Tape T-Soft

## Foam Tape

### :: DESCRIPTION

- Special foam tape
- Silicone-free glue
- Temperature resistant up to 80 °C / 1h

### :: AREA OF APPLICATION

- For closing gaps on doors, bonnets and trunk lids
- Protects inner areas from overspray

### :: BENEFITS

- Avoids hard paint edges
- Easy placement
- Perfect edge finish
- No glue residues

### :: PRODUCT DATA

#### Technical data

Material: Polypropylene, Polyethylene  
Length: 25 m  
Storage recommendation: max. 12 months at less than 35°C

# CS Foam Tape T-Soft

## Foam Tape

### :: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, expect we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery terms and conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE