

## ::: KS-50

sealing compound - brushable

### CHARACTERISTICS

Carsystem KS-50 Brushable Seam Sealer is a synthetic rubber-based sealant that can be applied with a paintbrush. This quick-drying product creates an elastic, heat and cold-resistant ( -25° C to +80° C) layer that can be painted over and is impervious to water and mineral spirits.

### APPLICATION

Waterproof sealing of joints, particularly when aftermarket body parts, covering trim pieces, etc. are installed in places that will later be painted. Body protection for weld seams.

### PRODUCT DATA

Packaging: 1 kg container

Color: Gray

Specific gravity: Approx. 1.2 kg/L

Drying time: 12 hours

Shelf life: At least 6 months

Quantity required: 1.2 kg/m<sup>2</sup>

The drying time depends on the layer thickness and ambient conditions. At 1mm wet layer thickness the drying time is ca. 12 hours (at 20°C and a relative humidity of 65%)

Solids content: Ca. 62%

### HANDLING



02/2019

The surface must be clean, dry, and free of grease and oil. Apply the product with a paintbrush on bare metal or primed/painted metal surfaces. Car System Brushable Seam Sealer will not drip or become stringy. You can paint over the sealer as soon as it dries. Do not apply at temperatures below 15°C.

### **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE